# AH-0218 & AH-9719



## Fire Alarm Bell & Indicating Lamp

### AH-0218 Fire Alarm Bell 6"

- High efficiency low current consumption on 24VDC motorized bells.
- Terminals will accept 2.5mm cables.
- Simple installation via multi-fixing base plate for all types of location.
- Fitted with two series diodes for fault monitoring.
- Option of customized discs printed with company name and logo.
- 12VDC bells are also available.

Approvals: EN54 LPCB C E





#### **Specifications** Model AH-0218 Dimensions ø6" (152mm) x 56mm(H) Vo**l**tage 24V DC Current 25mA Sound Output 93dB@1M Movement Motor, Pinion and striker Movement Features DC Motor, acetal gear wheel, steel striker Gong Steel, secured with phillips screw Base Plate Molded black polycarbonate Materia Steel plate Weight About 850g

#### **AH-9719 Fire Indicating Lamp**

- Uses white bulb (or low current LED) and installed inside the red lamp cover
- When lit, it is clear visible within 10 meters.

Approvals:

Specifications	
Model	AH-9719
Dimensions	90mm(Dia.) x 70mm(H)
Consumption Current	24V DC 60mA / LED 20mA
Bulb	30V/2W red bu <b>l</b> b or LED
Lamp Cover	Fire-proof plastic
Lamp Base	Fire-proof plastic
Weight	About 70g

